

Zebra® G-Series™ printers



Making a difference to your desktop

Zebra's G-Series compact desktop printers deliver best-in-class speed and performance for print widths up to 104mm (4"). From the basic GK™ model to the feature-rich GX™ model, the G-Series printers offer a reliable, durable and flexible desktop solution for any printing application and budget.

Built with Zebra durability and reliability, the G-Series GK model provides the best value of all basic desktop thermal printers, while the premier GX model supports a variety of industries and applications with the widest range of features. Choose the space-saving direct-thermal version of either model for the smallest footprint of any 104mm (4") desktop printer, or the direct-thermal/thermal-transfer version to save users time with the easiest ribbon-loading system available.

With both EPL™ and ZPL® native on all models and a variety of connectivity options for personal, local and networked systems, the G-Series printers integrate easily and seamlessly with other Zebra printing solutions.



Zebra's G-Series printers support many applications, including:

Healthcare:

- Patient identification
- Sample and specimen identification
- Sterile services labelling
- Pharmacy prescription labelling

Retail:

- Product labelling
- Price mark-down
- Shelf-edge labelling
- Voucher and receipt printing

Travel:

- Boarding passes
- Bag tags

Hospitality, Service & Leisure:

- Event and exhibition ticketing
- Fast-food labelling
- Gaming and betting slips

Supply chain:

- Process, product and
- shipping labelling

Post & parcel:

- Electronic franking
- Address labelling

Specifications at a glance*

Standard Features

- Print methods: Direct thermal or thermal transfer
- Programming languages: EPL and ZPL as standard
- Construction: Dual-wall frame
- Tool-less replacement of printhead and platen
- OpenACCESS™ for easy media loading
- Quick and easy ribbon loading
- Auto-calibration of media

Printer Specifications

Resolution

- 8 dots per mm/203dpi
- 12 dots per mm/300dpi (optional GX430t™)

Memory

- Standard: 4MB flash; 8MB SDRAM
- Optional: 64MB (68MB total) flash with RTC (GX models)

Print width

- 104mm/4.09"

Maximum print length

- 990mm/39.0"

Maximum print speed

- GK420: 127mm/5" per second
- GX420: 152mm/6" per second
- GX430: 102mm/4" per second

Media sensors

- Standard: Fixed reflective and transmissive sensors
- Adjustable reflective and multi-position transmissive sensor (GX models, optional)

Media Characteristics

Maximum label and liner length

- Maximum non-continuous: 990mm/39"

Maximum label and liner width

- 19mm/0.75" to 108mm/4.25"

Maximum media roll size

- 127mm/5" O.D.

Media thickness

- 0.076mm/0.003" to 0.19mm/0.0075"

Media types

- Roll-fed or fanfold, die-cut or continuous direct-thermal labels with or without black mark, tag stock, continuous receipt paper, wristbands

Ribbon Characteristics

Outside diameter

- 35mm/1.36"

Length

- 74m/244' (when using 0.08mm ribbon thickness)

Ratio

- 1:1 media roll to ribbon

Width

- 33.8mm/1.33" to 109.2mm/4.3"

Core inner diameter

- 12.7mm/0.5"

Operating Characteristics

Environmental

- Operating temperature: 4.4°C to 41°C
- Storage temperature: -40°C to 60°C
- Operating humidity: 5% to 95% non-condensing
- Storage humidity: 5% to 95% non-condensing

Electrical

- Auto-detectable (PFC-compliant) 100–240VAC, 50–60Hz

Agency Approvals

- Emissions: FCC Part 15, Subpart B, VCCI, C-Tick
- Emissions and Susceptibility: (CE): EN 55022 Class B, EN 61000-3-2, EN 61000-3-0 and EN 55024, CCC
- Safety: CB Scheme IEC 60950:1991 +A1 +A2 +A3 +A4, TÜV NRTL, IRAM NOM, AAMI, CCC

Physical Characteristics

Width

- Direct thermal 171mm/6.75"
- Thermal transfer 193mm/7.6"

Height

- Direct thermal 152mm/6.0"
- Thermal transfer 190mm/7.5"

Depth

- Direct thermal 210mm/8.25"
- Thermal transfer 254mm/10.0"

Weight

- Direct thermal 1.4kg/3lb
- Thermal transfer 2.1kg/4.6lb

ZebraLink™ Solutions

Software

- ZebraDesigner Driver (downloadable from www.zebra.com)
- ZebraDesigner™ Pro
- ZebraDesigner
- ZebraNet™ Bridge Enterprise
- ZebraNet Utilities v7.0
- Zebra Universal Driver
- POS Driver

Networking/Connectivity

- ZebraNet® 10/100 Print Server (optional)
- 802.11g wireless LAN (optional)
- Bluetooth® wireless PAN (optional)

Firmware

- EPL2™
- EPL Line Mode (Direct thermal only – GK420d and GX420d)
- ZPL II®
- Web View
- Alert

Communication and Interface Capabilities

GX models have triple interface standard

- RS-232 serial interface, DB-9
- USB 1.1, bi-directional

- Parallel DB-25 female connector, bi-directional
- ZebraNet 10/100 Print Server (optional) replaces parallel
- 802.11g wireless (optional)
- Bluetooth wireless (optional)
- Wireless options include LCD for visual communication

GK models have dual interface standard

- RS-232 serial interface, DB-9
- USB 1.1, bi-directional
- ZebraNet 10/100 Print Server (optional) replaces serial

Fonts/Graphics/Symbologies

Fonts and character sets

- 16 resident expandable ZPL II bitmap fonts
- One resident scalable ZPL font
- Five resident expandable EPL2 fonts
- Native OpenType™ font support
- Unicode™-compliant for multi-language applications

Graphics features

- Supports user-defined fonts and graphics including custom logos
- ZPL II drawing commands for boxes and lines

Bar code symbologies

- Bar code ratios: 2:1 (non-rotated) and 3:1
For EPL and ZPL except where noted
- Linear Bar Codes: Codabar, Code 11 (ZPL), Code 39, Code 93, Code 128, EAN-8, EAN-13, EAN-14 (ZPL), German Post Code (EPL), GS1 DataBar (RSS), Industrial 2-of-5 (ZPL), Interleaved 2-of-5, ISBT-128 (ZPL), Japanese Postnet (EPL), Logmars (ZPL), MSI, Plessey, Postnet, Standard 2-of-5 (ZPL), UCC/EAN-128 (EPL), UPC-A, UPC-A and UPC-E with EAN 2 or 5 digit extensions, UPC-E, UPC and EAN 2 or 5 digit extensions (ZPL)
- Two-dimensional: Codablock (ZPL), Code 49 (ZPL), Data Matrix, (ZPL), MaxiCode, MicroPDF417, PDF417, QR Code

Options And Accessories

- Label dispenser with label-present sensor
- ZebraNet 10/100 Print Server – internal Ethernet for network communication and printing
- 802.11g wireless (optional)
- Bluetooth wireless (optional)
- Wireless options include LCD for visual communication
- Adjustable media sensor (GX models)
- Cutter for various media types (GX models)
- 300dpi print resolution printing for fine detail and crisp images (GX430t)
- 64MB flash memory with real-time clock for total of 68MB (GX models)
- Font packs – Asian and other international font kits
- KDU Plus™ and KDU™ keyboard display units for standalone printing solutions
- Interface cables and adapters

*Specifications subject to change without notice.

©2009 ZIH Corp. Energy Element Equalizer, ZebraDesigner, ZebraLink, ZebraNet and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head, E³, ZebraNet and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Mifare is a registered trademark of Philips Semiconductors Gratkorn GmbH Ltd. Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and/or other countries. CompactFlash is a registered trademark of SanDisk Corporation. CG Triumvirate is a trademark of Monotype Imaging, Inc. IBM is a registered trademark of International Business Machines Corporation. Unicode is a trademark of Unicode, Inc. All other trademarks are the property of their respective owners.



Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom
Telephone: +44 (0)1628 556000 **Fax:** +44 (0)1628 556001 **E-mail:** mseurope@zebra.com **Web:** www.zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden **Middle East & Africa:** Dubai, South Africa