

DNP TR3021, 22, 23



Thermal Transfer Ribbon Technical Data Sheet

TR3021, 22, 23 General Purpose Wax

Red Blue Green

Product Description

Based on DNP's proven wax technology, these quality ribbons expand your color possibilities while providing excellent print clarity and high smudge resistance when black just isn't enough. These ribbons are also specially formulated with DNP's backcoat technology for printhead protection.



TR3021 Red
PMS 1787C




TR3022 Blue
PMS 286C



TR3023 Green
PMS 3405C

Colors may vary by substrate
PMS = Pantone Matching System

Recommended Applications



COLOR



GENERAL



HORTICULTURE



INVENTORY



OUTDOOR



PARTS
PACKAGING



PRODUCT ID



RETAIL



SHELF



SIGNAGE

Recommended Substrates

Coated/uncoated paper & tag stocks, synthetic paper, polyethylene, polypropylene, top-coated vinyl, polyolefin, Tyvek®, Tyvek Brillion®

Performance Characteristics

- Halogen-Free (TR3022 Blue)
- Provides excellent print clarity and is highly smudge resistant
- Prints at high speeds (12 IPS) delivering crisp, rotated bar codes
- Features DNP's SmoothCoat® backcoat
- Unbeatable edge definition for dark, dense images and improved scan rates

The information on this data sheet was obtained in DNP IMS America laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

Visit us at www.dnpribbons.eu

DNP IMS Netherlands B.V.

Oudeweg 42

2031CC Haarlem

THE NETHERLANDS

TEL: +31.(0)23 553 30 80

FAX: +31.(0)23 551 52 32

EMAIL: sales@dnpribbons.eu

DNP Global Locations

USA

Japan

Netherlands

Singapore



Thermal Transfer Ribbon Technical Data Sheet

TR3021, 22, 23 General Purpose Wax Red Blue Green

Ribbon Properties

Description	Result	Test Method
Ink	Wax	
Color	Red, Blue, Green	Visual
Total Thickness	8.4 ± 0.5µ	Micrometer
Base Film Thickness	4.8 ± 0.3µ	Micrometer
Ink Thickness	3.6 ± 0.2µ	Micrometer
Ink Melting Point	72°C (162°F)	Differential Scanning Calorimeter

Durability of Printed Image

Label Stock: Coated Paper

Print Speed: 6 IPS

Description	Result			Test Method
	Y	M	C	
Print Density - Red	0.84 - 1.18	1.24 - 1.90	0.01 - 0.26	Densitometer
Print Density - Blue	0.08 - 0.56	0.85 - 1.57	1.18 - 1.94	Densitometer
Print Density - Green	0.63 - 1.41	0.28 - 0.50	1.47 - 2.15	Densitometer

Conversion Chart

Millimeters (mm) to Inches = mm ÷ 25.4	Inches to Millimeters (mm) = Inches ÷ 0.03937
Meters (m) to Feet (ft) = m ÷ 0.3048	Feet (ft) to Meters (m) = Feet ÷ 3.2808
C° to F° = (1.8 X C°) + 32 = F°	F° to C° = (F° ÷ 1.8) - 17.77
Thousand square inches (MSI) to m ² = MSI X 0.645	MSI = m ² ÷ 0.645



The information on this data sheet was obtained in DNP IMS America laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

Visit us at www.dnpribbons.eu

DNP IMS Netherlands B.V.
Oudeweg 42
2031CC Haarlem
THE NETHERLANDS
TEL: +31.(0)23 553 30 80
FAX: +31.(0)23 551 52 32
EMAIL: sales@dnpribbons.eu

