



## Flex-Matic



The Flex-Matic has been developed to accurately apply labels to a wide range of flat products including Bags, Envelopes, Pamphlets, PCB's etc. up to a maximum thickness of 4mm.

It is easily set to position the labels horizontally and vertically on the products (minimum of 19mm from the leading edge vertically.)

It is possible to apply labels to continuous media providing a cut out is included to activate the feed sensor.

Most self adhesive materials can be applied including polymers and book labels but we always recommend testing them before purchase.

***For more information & prices contact:***

## **Product Specification**

<b>Media Thickness:</b>	Up to a maximum of 4mm
<b>Media Width:</b>	Recommended minimum of 25mm and a maximum of 350mm
<b>Media Length:</b>	Any length (can be continuous with slot)
<b>Label Width:</b>	Recommended minimum of 25mm and a maximum of 350mm
<b>Label Roll Diameter:</b>	Standard 22cm, (with optional roll adaptor up to 38cm)
<b>Label Roll Core:</b>	76mm internal diameter (full width of backing paper recommended)
<b>Positioning Accuracy:</b>	+ or – 2mm adjustable in 1mm increments
<b>Operation:</b>	Manual loading with automatic feed at approximately 7 metres per minute
<b>Electrical Supply:</b>	230V 50HZ (115v 60HZ available on request)
<b>Dimensions:</b>	55cm long x 43cm wide x 20cm high
<b>Weight:</b>	18kg.

Constructed to the highest engineering standards and comes complete with a 2 year warranty against manufacturing defects and are fully compliant with all current safety standards.



***For more information & prices contact:***