





RWG500

Intelligent and Silent Rewinder



Auto-adjustable winding speed corresponds to the label print speed



Noise level below 60dB



Auto-adjustable winding



User-friendly Operation Panel



Up to 6" (inch) Label width Support

RWG500

General Specifications

OPERATION CHARACTERISTICS

Environment	Operating	0 ~ 40°C / 30 ~ 80% (without condensation)
	Storage	-5 ~ 60°C / 30 ~ 90% (without condensation)
Regulatory approvals		UL/C-UL, FCC, CE, TUV, CCC
Dimension (W x D x H), weight		280 mm x 320 mm x 230 mm, ~7.5kg
Noise level		Less than 60 dB
Input power		DC_24V, 2A
Printer connection		Connection Cable for SATO printers with EXT interface. Joint Plate for SATO M5900RVe, LM4xxe, CL4xxe, GT4xxe, GL4xxe, CL6xxe (CL6xxe can be used only when media width is 131 mm or less)

WINDING CHARACTERISTICS

Winding speed		Maximum 381 mm/sec (max. 15 inch/sec)
Winding method		38,1 mm (1,5") core (Direct Rewind) / 76 mm (3") core (Using Paper-core)
Winding direction		Face-out/face-in (Counterclockwise / Clockwise)
Winding monitoring		Winding ON/OFF by tension arm position
Winding outer diameter		Maximum winding OD up to 265 mm (11 inch)
Media size	Width, mm	25 - 131 (option 132 - 180)
	Pitch, mm	8 - 400
	Thickness, mm	0.08 - 0.27

OPTION

Rewinder kit	6" extension kit Power supply for SATO printers without EXT interface or for usage with non-SATO printers
--------------	--

Printer Compatibility



CL6xxe



CL4xxe & LM4xxe



M-84Pro



M5900VRVe



GTe408e & GL4xxe